



Version Revision Date: SDS Number: Date of last issue: -

1.0 28.11.2023 50001594 Date of first issue: 28.11.2023

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Deadmag® Blowfly Strike Dressing Fluid

Recommended use of the chemical and restrictions on use

Recommended use : For the treatment of blowfly struck sheep.

Restrictions on use : Use as recommended by the label.

Manufacturer or supplier's details

Company : FMC Australasia Pty Ltd

Address : Building B, Level 2, 12 Julius Avenue,

North Ryde NSW 2113

Australia

Telephone : 1 800 066 355

Telefax : (02)9923 6011

E-mail address : SDS-Info@fmc.com

Emergency telephone number : For leak, fire, spill or accident emergencies, call:

1800 033 111 (Ixom)

Medical emergency:

1 800 033 111 (Transport and 24 h Medical information)

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 3

Serious eye damage/eye irri-

tation

Category 1

Carcinogenicity : Category 2

Specific target organ toxicity - :

single exposure

Category 3 (Central nervous system)

Aspiration hazard : Category 1

GHS label elements





Version Revision Date: SDS Number: Date of last issue: -

1.0 28.11.2023 50001594 Date of first issue: 28.11.2023

Hazard pictograms









Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H318 Causes serious eye damage. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer.

Supplemental Hazard State-

ments

AUH066 Repeated exposure may cause skin dryness or crack-

ing.

Precautionary statements : Pre

Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equip-

ment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P261 Avoid breathing mist or vapours.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P331 Do NOT induce vomiting.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.





Version Revision Date: SDS Number: Date of last issue: -

1.0 28.11.2023 50001594 Date of first issue: 28.11.2023

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Propetamphos	31218-83-4	< 10
1,4-dichlorobenzene	106-46-7	> 30 -< 60
4-Nonylphenol branched, ethoxylated	127087-87-0	> 5 -< 20
Solvent naphtha (petroleum), heavy arom.;	64742-94-5	> 30 -< 60
Kerosine — unspecified		

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later.

Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : If on skin, rinse well with water.

If on clothes, remove clothes.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Keep respiratory tract clear. Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.





Version **Revision Date:** SDS Number: Date of last issue: -

28.11.2023 50001594 Date of first issue: 28.11.2023 1.0

Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

May be fatal if swallowed and enters airways.

Causes serious eye damage.

May cause drowsiness or dizziness.

Suspected of causing cancer.

Repeated exposure may cause skin dryness or cracking.

Notes to physician Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire-

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod-

ucts

Fire may produce irritating, corrosive and/or toxic gases.

Specific extinguishing meth-

ods

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

For safety reasons in case of fire, cans should be stored sepa-

rately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment :

for firefighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

Hazchem Code •3Y

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : tive equipment and emer-

gency procedures

Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

Prevent product from entering drains. **Environmental precautions**

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, ver-





Version Revision Date: SDS Number: Date of last issue: -

1.0 28.11.2023 50001594 Date of first issue: 28.11.2023

miculite) and place in container for disposal according to local

/ national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on protection against :

fire and explosion

Do not spray on a naked flame or any incandescent material.

Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).

Keep away from open flames, hot surfaces and sources of

ignition.

Advice on safe handling : Avoid formation of aerosol.

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. To avoid spills during handling keep bottle on a metal tray. Dispose of rinse water in accordance with local and national

regulations.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

Conditions for safe storage : No smoking.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Solvent naphtha (petroleum), heavy arom.; Kerosine — un- specified	64742-94-5	TWA	200 mg/m3 (total hydrocarbon vapor)	ACGIH
1,4-dichlorobenzene	106-46-7	TWA	25 ppm 150 mg/m3	AU OEL





Version Revision Date: SDS Number: Date of last issue: -

1.0 28.11.2023 50001594 Date of first issue: 28.11.2023

Further information: Category 2 (Carc. 2) Suspected human carcinogen				
	STEL	50 ppm 300 mg/m3	AU OEL	
Further information: Category 2 (Carc. 2) Suspected human carcinogen				
	TWA	10 ppm	ACGIH	

Personal protective equipment

Respiratory protection : In case of mist, spray or aerosol exposure wear suitable per-

sonal respiratory protection and protective suit.

Hand protection

Material : Wear chemical resistant gloves, such as barrier laminate,

butyl rubber or nitrile rubber.

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Form : liquid

Colour : colourless

Odour : mild, characteristic

pH : not determined

Melting point/freezing point : not determined

Boiling point/boiling range : not determined

Flash point : 54 °C

Method: closed cup

Self-ignition : No data available



Deadmag® Blowfly Strike Dressing Fluid

Version Revision Date: SDS Number: Date of last issue: -

1.0 28.11.2023 50001594 Date of first issue: 28.11.2023

Vapour pressure : not determined

Density : 1.016 g/cm3

Solubility(ies)

Water solubility : emulsifiable

Partition coefficient: n-

octanol/water

Not applicable

Viscosity

Viscosity, kinematic : not determined

Explosive properties : Not explosive

Oxidizing properties : Non-oxidizing

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reac-

tions

No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Strong oxidizing agents

Strong acids and strong bases

Hazardous decomposition

products

Stable under recommended storage conditions.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified due to lack of data.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Components:

Propetamphos:



Deadmag® Blowfly Strike Dressing Fluid

Version Revision Date: SDS Number: Date of last issue: -

1.0 28.11.2023 50001594 Date of first issue: 28.11.2023

Acute oral toxicity : LD50 (Rat): 75 - 110 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 2.04 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The component/mixture is minimally toxic after

short term inhalation.

Acute dermal toxicity : LD50 (Rat): > 2,300 mg/kg

LD50 (Rabbit): > 10,000 mg/kg

1,4-dichlorobenzene:

Acute oral toxicity : LD50 (Rat, male and female): > 2,000 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat, male and female): > 5.07 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Assessment: The component/mixture is minimally toxic after

short term inhalation.

Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

4-Nonylphenol branched, ethoxylated:

Acute oral toxicity : LD50 (Rat): > 300 - 2,000 mg/kg

Acute inhalation toxicity : Assessment: The component/mixture is moderately toxic after

short term inhalation.

Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:

Acute oral toxicity : LD50 (Rat, male and female): > 5,000 mg/kg

Method: OECD Test Guideline 401

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat, male and female): > 5.28 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit, male and female): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: Based on data from similar materials



Deadmag® Blowfly Strike Dressing Fluid

Version Revision Date: SDS Number: Date of last issue: -

1.0 28.11.2023 50001594 Date of first issue: 28.11.2023

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Product:

Remarks : Extremely corrosive and destructive to tissue.

Components:

1,4-dichlorobenzene:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Remarks : Based on available data, the classification criteria are not met.

4-Nonylphenol branched, ethoxylated:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:

Species : Rabbit

Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Remarks : May cause irreversible eye damage.

Components:

1,4-dichlorobenzene:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

4-Nonylphenol branched, ethoxylated:

Species : Rabbit

Result : Irreversible effects on the eye Method : OECD Test Guideline 405

Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:

Species : Rabbit

Result : No eye irritation

Remarks : Based on data from similar materials



Deadmag® Blowfly Strike Dressing Fluid

Version Revision Date: SDS Number: Date of last issue: -

1.0 28.11.2023 50001594 Date of first issue: 28.11.2023

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Components:

1,4-dichlorobenzene:

Test Type : Maximisation Test Exposure routes : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406 Result : Not a skin sensitizer.

Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:

Test Type : Buehler Test Species : Guinea pig

Result : Does not cause skin sensitisation.
Remarks : Based on data from similar materials

Chronic toxicity

Germ cell mutagenicity

Not classified due to lack of data.

Components:

1,4-dichlorobenzene:

Genotoxicity in vitro : Test Type: reverse mutation assay

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Genotoxicity in vivo : Test Type: Micronucleus test

Species: mice (male and female)

Application Route: Oral

Result: negative

Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:

Genotoxicity in vitro : Test Type: reverse mutation assay

Result: negative

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: sister chromatid exchange assay

Species: Mouse

Application Route: Intraperitoneal injection

Result: negative

Remarks: Based on data from similar materials



Deadmag® Blowfly Strike Dressing Fluid

Version Revision Date: SDS Number: Date of last issue: -

1.0 28.11.2023 50001594 Date of first issue: 28.11.2023

Carcinogenicity

Suspected of causing cancer.

Components:

1,4-dichlorobenzene:

Carcinogenicity - Assess-

ment

: Limited evidence of carcinogenicity in animal studies

Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:

Species : Mouse
Application Route : Dermal
Exposure time : 104 weeks
Result : negative

Remarks : Based on data from similar materials

Carcinogenicity - Assess-

ment

Limited evidence of carcinogenicity in animal studies

Reproductive toxicity

Not classified due to lack of data.

Components:

Propetamphos:

Reproductive toxicity - As-

sessment

Suspected of damaging fertility or the unborn child.

1,4-dichlorobenzene:

Effects on fertility : Test Type: Two-generation study

Species: Rat, male and female Application Route: Ingestion Fertility: NOAEL: 270 mg/kg bw/day Method: OECD Test Guideline 416

Remarks: No significant adverse effects were reported

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rabbit

Application Route: Inhalation

General Toxicity Maternal: NOAEC: 300 part per million Teratogenicity: NOAEC F2: >= 800 part per million

Result: negative

Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:

Effects on fertility : Test Type: Fertility

Species: Rat, male and female

Application Route: Oral

Method: OECD Test Guideline 415

Result: negative

Remarks: Based on data from similar materials

Effects on foetal develop-

ment

Test Type: reproductive and developmental toxicity study

Species: Rat



Deadmag® Blowfly Strike Dressing Fluid

Version Revision Date: SDS Number: Date of last issue: -

1.0 28.11.2023 50001594 Date of first issue: 28.11.2023

Application Route: Oral

Method: OECD Test Guideline 414

Result: negative

Remarks: Based on data from similar materials

STOT - single exposure

May cause drowsiness or dizziness.

Components:

Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:

Assessment : May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified due to lack of data.

Repeated dose toxicity

Components:

1,4-dichlorobenzene:

Species : Rat, male and female

NOAEL : < 75 mg/kg
Application Route : Oral - gavage
Exposure time : 13 weeks

Remarks : No toxicologically significant effects were found.

Species : Rat, male and female

NOAEC : 75 ppm

Application Route : inhalation (vapour)

Exposure time : 2 years

Method : OECD Test Guideline 453

Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:

Species : Rat, male and female

NOAEL : 750 mg/kg
Application Route : Oral - gavage
Exposure time : 90 day

Remarks : Based on data from similar materials

Species : Rat, male and female

NOAEL : 1 mg/l LOAEL : 0.5 mg/l

Application Route : inhalation (vapour)

Exposure time : 90 day

Symptoms : Alpha-2u-globulin nephropathy

Aspiration toxicity

May be fatal if swallowed and enters airways.



Deadmag® Blowfly Strike Dressing Fluid

Version Revision Date: SDS Number: Date of last issue: -

1.0 28.11.2023 50001594 Date of first issue: 28.11.2023

Components:

Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Further information

Product:

Remarks : Symptoms of overexposure may be headache, dizziness,

tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause

narcotic effects.

Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Propetamphos:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 1.3 mg/l

Exposure time: 96 h

LC50 (Oncorhynchus mykiss (rainbow trout)): 0.36 mg/l

Exposure time: 96 h

LC50 (Cyprinus carpio (Carp)): 3.7 - 8.8 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

LC50 (Daphnia magna (Water flea)): 0.68 - 14.5 mg/l

Exposure time: 48 h

1,4-dichlorobenzene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 1.12 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 0.7 mg/l

Exposure time: 48 h Test Type: static test

Toxicity to algae/aquatic

plants

71

NOEC (Raphidocelis subcapitata (freshwater green alga)): 0.57 mg/l

Exposure time: 96 h Test Type: static test

EC50 (Raphidocelis subcapitata (freshwater green alga)): 1.6

mg/l

Exposure time: 96 h Test Type: static test



Deadmag® Blowfly Strike Dressing Fluid

Version **Revision Date:** SDS Number: Date of last issue: -

28.11.2023 50001594 Date of first issue: 28.11.2023 1.0

Toxicity to fish (Chronic tox-

icity)

NOEC (Jordanella floridae (flagfish)): 0.2 - 0.23 mg/l

Exposure time: 16 d

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 0.22 mg/l

Exposure time: 28 d Test Type: semi-static test

Ecotoxicology Assessment

Chronic aquatic toxicity Very toxic to aquatic life with long lasting effects.

4-Nonylphenol branched, ethoxylated:

LC50 (Zebra fish): 1 - 10 mg/l Toxicity to fish

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to microorganisms EC50 (Bacteria): > 1,000 mg/l

Ecotoxicology Assessment

Acute aquatic toxicity Toxic to aquatic life.

Chronic aquatic toxicity Toxic to aquatic life with long lasting effects.

Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:

Toxicity to fish LL50 (Oncorhynchus mykiss (rainbow trout)): 2 - 5 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: water accommodated fractions (WAF)

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): 1.4 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Remarks: water accommodated fractions (WAF)

Toxicity to algae/aquatic

plants

EL50 (Pseudokirchneriella subcapitata (green algae)): > 1 - 3

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: water accommodated fractions (WAF)

LL50 (Tetrahymena pyriformis): 677.9 mg/l Toxicity to microorganisms

Exposure time: 72 h

Test Type: Growth inhibition

Persistence and degradability

Components:

1,4-dichlorobenzene:

Biodegradability Result: Readily biodegradable.

> Biodegradation: 100 % Exposure time: 28 d



Deadmag® Blowfly Strike Dressing Fluid

Version Revision Date: SDS Number: Date of last issue: -

1.0 28.11.2023 50001594 Date of first issue: 28.11.2023

4-Nonylphenol branched, ethoxylated:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 86 % Exposure time: 28 d

Method: OECD Test Guideline 301E

Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:

Biodegradability : Result: Inherently biodegradable.

Biodegradation: 58.6 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Remarks: Based on data from similar materials

Bioaccumulative potential

Components:

1,4-dichlorobenzene:

Partition coefficient: n-

octanol/water

log Pow: 3.37 (25 °C)

Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:

Partition coefficient: n- : log Pow: 1.99 - 18.02 octanol/water : Method: QSAR

Mobility in soil
No data available

Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Very toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.



Deadmag® Blowfly Strike Dressing Fluid

Version Revision Date: SDS Number: Date of last issue: -

1.0 28.11.2023 50001594 Date of first issue: 28.11.2023

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 1993

Proper shipping name : FLAMMABLE LIQUID, N.O.S.

(Solvent naphtha (petroleum), heavy arom.)

Class : 3
Packing group : III
Labels : 3

IATA-DGR

UN/ID No. : UN 1993

Proper shipping name : Flammable liquid, n.o.s.

(Solvent naphtha (petroleum), heavy arom.)

Class : 3 Packing group : III

Labels : Flammable Liquids

Packing instruction (cargo : 366

aircraft)

Packing instruction (passen- : 355

ger aircraft)

Environmentally hazardous : yes

IMDG-Code

UN number : UN 1993

Proper shipping name : FLAMMABLE LIQUID, N.O.S.

(Solvent naphtha (petroleum), heavy arom.)

Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

ADG

UN number : UN 1993

Proper shipping name : FLAMMABLE LIQUID, N.O.S.

(Solvent naphtha (petroleum), heavy arom.)

Class : 3
Packing group : III
Labels : 3
Hazchem Code : •3Y

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.





Version Revision Date: SDS Number: Date of last issue: -

1.0 28.11.2023 50001594 Date of first issue: 28.11.2023

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Standard for the Uniform

Scheduling of Medicines and

Poisons

Schedule 6

APVMA Code: 40138

Prohibition/Licensing Requirements

There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regula-

tions.

The components of this product are reported in the following inventories:

TCSI : On the inventory, or in compliance with the inventory

TSCA : Product contains substance(s) not listed on TSCA inventory.

AIIC : Not in compliance with the inventory

DSL : This product contains the following components that are not

on the Canadian DSL nor NDSL.

Propetamphos

ENCS : Not in compliance with the inventory

ISHL : On the inventory, or in compliance with the inventory

KECI: On the inventory, or in compliance with the inventory

PICCS : Not in compliance with the inventory

IECSC : Not in compliance with the inventory

NZIoC : Not in compliance with the inventory

TECI: On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Revision Date : 28.11.2023

Date format : dd.mm.yyyy



Deadmag® Blowfly Strike Dressing Fluid

Version Revision Date: SDS Number: Date of last issue: -

1.0 28.11.2023 50001594 Date of first issue: 28.11.2023

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

AU OEL : Australia. Workplace Exposure Standards for Airborne Con-

taminants.

ACGIH / TWA : 8-hour, time-weighted average

AU OEL / TWA : Exposure standard - time weighted average AU OEL / STEL : Exposure standard - short term exposure limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Disclaimer

FMC Corporation believes that the information and recommendations contained herein (including data and statements) are accurate as of the date hereof. You can contact FMC Corporation to ensure that this document is the most current available from FMC Corporation. No warranty of fitness for any particular purpose, warranty of merchantability or any other warranty, expressed or implied, is made concerning the information provided herein. The information provided herein relates only to the specified product designated and may not be applicable where such product is used in combination with any other materials or in any process. The user is responsible for determining whether the product is fit for a particular purpose and suitable for the user's conditions and methods of use. Since the conditions and methods of use are beyond the control of FMC Corporation, FMC Corporation expressly disclaims any and all liability as to any results obtained or arising from any use of the products or reliance on such information.

AU / 6N